

3M™ Protective Coverall 4565

Technical Datasheet



Description

The 3M™ Protective Coverall 4565 coverall is designed to help protect against: hazardous dusts (Type 5); certain light liquid splashes (Type 6) and certain light liquid sprays (Type 4).

Comfort and protection



Liquid protection

Type 6 - Light Liquid Splashes
(EN 13034:2005 + A1:2009)



Liquid protection

Type 4 - Liquid Spray
(EN 14605:2005 + A1:2009)



Dust protection

Type 5 - Solid Airborne Particulates
(EN ISO 13982-1:2004 +A1:2010)



Anti-static

Anti-static coating* on inner surface
(EN 1149-5:2008)



Nuclear


Radioactive particulates Class 2
(EN 1073-2:2002 except EN 863 puncture)



Biohazard

Types 5-B and 6-B - Infective Agents
(EN 14126:2003 except ISO 16604)

* All apparel must be suitably grounded for anti-static treatment to be effective.



Sizing

An appropriate size garment should be selected to allow sufficient movement for the task whilst maintaining a secure fit.

	Height		Chest	
S	64 – 67 in	164 – 170 cm	33 - 36 in	84 – 92 cm
M	66 – 69 in	167 – 176 cm	36 – 39 in	92 – 100 cm
L	69 – 71 in	174 – 181 cm	39 – 43 in	100 – 108 cm
XL	70 – 74 in	179 – 187 cm	43 – 45 in	108 – 115 cm
XXL	73 – 76 in	186 – 194 cm	45 – 49 in	115 – 124 cm
3XL	76 – 78 in	194 – 200 cm	49 – 52 in	124 – 132 cm
4XL	78 – 81 in	200 – 206 cm	52 – 55 in	132 – 140 cm



Approvals

These products are type examined by SATRA Technology Europe Ltd., Notified Body number 2777 and audited annually by SGS, Notified Body number 0598.

These products are CE marked to the requirements of European Regulation (EU) 2016/425.

The CE Certificate and Declaration of Conformity can be reviewed at www.3m.com/Body/certs

Materials

Suit	Polyethylene + polyester / polyethylene laminate
Zipper	Metal/nylon/polyester braid
Elastic	Neoprene rubber
Cuffs	Polyester
Thread	Polyester/cotton
Tape	Polypropylene, red

This product does not contain components made from natural rubber latex.

Storage and disposal

- ▶ Store in dry, clean conditions in original packaging, away from direct sunlight, sources of high temperature, and solvent vapours
- ▶ Store within the temperature range -20°C to +25°C (-4°F to +77°F) and with relative humidity below 80%
- ▶ Expected shelf life is seven (7) years from date of manufacture when stored as stated
- ▶ Replace garments if damaged, heavily contaminated or in accordance with local work practice or regulations
- ▶ Handle and dispose of contaminated garments with care and in accordance with applicable regulations

Limited use



Do not wash



Do not dry clean



Do not bleach



Flammable — keep away from sparks or flames



Do not iron



Single use — do not re-use



Do not tumble dry

Warnings and limitations

Before use read and understand all user instructions and be sure that the product is suitable for the application and fitted correctly. Product must never be altered or modified.

Do not use for:

- ▶ Contact with heavy oils, sparks or flame, or combustible liquids;
- ▶ Environments with high mechanical risks (abrasions, tears, cuts);
- ▶ Contact with hazardous substances beyond Type 4/5/6 certification;
- ▶ Environments with conditions of excessive heat

Applications and performance

Non-Hazardous Particulates	Yes	Hazardous Liquid Splash	Yes, if chemical is compatible with suit material [†]
Non-Hazardous Liquid Splash	Yes	Hazardous Liquid Spray	Yes, if chemical is compatible with suit material [†]
Non-Hazardous Liquid Spray	Yes	Hazardous Dusts and Fibres	Yes
Liquid Continuous Contact/Immersion	No	Organic Solvents	Yes, if chemical is compatible with suit material [†]
Gases and Vapours	No	Acids/Alkalis	Yes, if chemical is compatible with suit material [†]

[†] The chemicals against which the product has been tested and certified are listed in the user instructions and shown in the following table. For additional chemical penetration data, please call your local 3M Technical Service Representative or visit the 3M Chemical Test library on <http://go.3M.com/CHTL>

In all cases, a risk assessment should be carried out. Always read product user information. Use limitations and performance data should be considered to ascertain the protection required. If in doubt, contact a safety professional.

The table below shows the performance of this product when tested under laboratory conditions in accordance with the referenced standard test method. Note: The maximum Class is 6 unless otherwise noted.

Test	Standard/test method	Class/result
Abrasion resistance (visual assessment)	EN530:2010	Class 1
Flex cracking (visual assessment)	ISO 7854:1995	Class 1
Tear resistance	ISO 9073-4:1997	Class 1
Tensile strength	EN ISO 13934-1:1999	Class 1
Puncture resistance	EN 863:1995	Class 1
Bursting resistance	ISO 13938-2:1999	Class 1
Resistance to ignition	EN 13274-4:2001	Pass
Resistance to blocking	EN 25978:1990	No blocking
Seam strength	EN ISO 13935-2:199	Class 2
Repellency to liquids – 30% H ₂ SO ₄	EN ISO 6530:2005	Class 3 of 3
Liquid penetration resistance – 30% H ₂ SO ₄	EN ISO 6530:2005	Class 3 of 3
Repellency to liquids – 10% NaOH	EN ISO 6530:2005	Class 3 of 3
Liquid penetration resistance – 10% NaOH	EN ISO 6530:2005	Class 3 of 3
Anti-static coating on both sides	EN 1149-1:2006	Pass
Radioactive particulates (TIL)	EN 1073-2:2002	Class 1 of 3
Biological protection	EN 14126:2003	
Synthetic blood penetration resistance	ISO 16603:2004	Pass 20kPa
Blood-borne pathogen penetration resistance	ISO 16604:2004	Unclassified
Contaminated solid particle penetration resistance	ISO 22612:2005	Class 3 of 3
Contaminated liquid aerosol penetration resistance	ISO/DIS 22611:200	Class 3 of 3
Wet bacteria penetration resistance	EN ISO 22610:2006	Class 6

For more information on 3M products and services please contact 3M.

IMPORTANT NOTICE

The use of the 3M product described within this document assumes that the user has previous experience of this type of product and that it will be used by a competent professional. Before any use of this product it is recommended to complete some trials to validate the performance of the product within its expected application.

All information and specification details contained within this document are inherent to this specific 3M product and would not be applied to other products or environment. Any action or usage of this product made in violation of this document is at the risk of the user.

Compliance to the information and specification relative to the 3M product contained within this document does not exempt the user from compliance with additional guidelines (safety rules, procedures). Compliance to operational requirements especially in respect to the environment and usage of tools with this product must be observed. The 3M group (which cannot verify or control those elements) would not be held responsible for the consequences of any violation of these rules which remain external to its decision and control.

Warranty conditions for 3M products are determined with the sales contract documents and with the mandatory and applicable clause, excluding any other warranty or compensation.

Personal Safety Division
3M Centre
Cain Road, Bracknell
Berkshire RG12 8HT

www.3M.eu/safety

3M is a trademark of 3M Company.
Please recycle. Printed in the United Kingdom.
© 3M 2020. All rights reserved.
OMG70831

